

- 1 Ea. New latest model Self-Propelled Highway Sweeper; meeting the following specifications, in accordance with manufacturer's standard published specifications:

Main Frame: All welded heavy structural steel.

Overall Width for Transport: 85-100 inches.

Overall Height (with ROPS or Cab): Not to exceed 100 inches.

Inside Turning Radius: Under 10 feet.

Brakes: Hydraulic Brakes.
Mechanical Parking Brakes.

Front Mounted Broom:
Broom Core: Length 7 feet 6 inches
10" I.D. x 32" O.D. 1/2 poly and 1/2 steel

Sweeping Angle: 30 degrees right or left.
140 degree Metal Core Cover.

Hydraulic System: Tank Capacity - 20 gallons
Filter - Replaceable Element

Engine: 80 H.P. Diesel
Dual element dry type air cleaner with turbine type pre-cleaner and at least cab height air intake.

Fuel Capacity: 20 gallons minimum

Transmission: Hydrostatic Drive or Hydraulic & Mechanical

Axles: Truck type axles w/rear steering and oscillating.

Equipped with the following: Water sprinkling system to include at least 120 gallon tank and pumping system; R.O.P.S fully enclosed Cab with safety glass; cab heater; air conditioner; defroster fan; windshield wiper; filtered air pressurizer; reverse signal alarm; light group; electric hour meter; electric tachometer; and revolving beacon light - H.D. amber lens, cab suspension seat, vandalize package, west coast and 8" convex mirrors, and front windshield washer.

Vendor to furnish two (2) sets of parts books, service manuals, technical manuals, and operators' manuals with unit.

Delivery date may be a factor in making award.

Must have
three (3) sets of keys.